




1M Mortise Dead Lock

SPECIFICATIONS

- Certifications** UL Listed for 3-Hour fire rating, ANSI A156.5, Grade 1
- Case** Heavy wrought steel with zinc dichromate finish, field reversible handing, self-adjusting face for beveled doors.
Full Case: 4 5/16" x 6" x 1"
Small Case: 4 5/16" x 3 9/16" x 1"
- Deadbolt** 1" throw, stainless steel
- Backset** 2 3/4"
- Door Range** 1 3/8" to 2 1/2" thick doors
- Strikes** Full Case: 1-1/4" x 4-7/8", curved lip, non-handed, furnished with dust box
Small Case: 1 1/8" x 3 1/2", no lip, non-handed, furnished with dust box
- IC Core** OAK Interchangeable 6 or 7-pin core compatible with all other SFIC housings.
- IC Cylinder** Standard 7 pin interchangeable core housing, compatible with all SFIC cores.
- Non IC Cylinder** Standard "C" keyway, Compatible with Schlage
- Masterkeying** Tailored masterkey system set-up and design, construction cores available.
- Finishes** 605 (bright brass), 606 (satin brass), 612 (satin bronze), 613 (dark bronze), 625 (bright chrome), 626 (satin chrome)



FUNCTIONS

FUNCTION	DESCRIPTION	ANSI NUMBER
CD	Classroom Lock Deadbolt thrown or retracted by key from outside. Inside thumbturn cylinder retracts deadbolt but cannot project it.	E06091
KD	Cylinder x Thumbturn Lock Deadbolt thrown or retracted by key outside or thumbturn inside.	E06071
MD	Double Cylinder Lock* Deadbolt operated by key from either side.	E06061
TD	Door Bolt Deadbolt thrown or retracted by thumbturn from one side. No trim on opposite side.	E06181
LD	Cylinder Lock Deadbolt thrown or retracted by key from one side. No trim on opposite side.	E06081

***Caution:** Double cylinder locks on residences and any door in any structure which is used for egress are a life safety hazard in times of emergency and their use is not recommended. Installation should be in accordance with existing codes only.

**Manufacturers' registered trade names used above are for identification and reference only.*