



41SP SHROUDED PADLOCK

FEATURES

- Solid stainless steel case, combined with a stainless shackle provide industry leading corrosion protection for the most demanding environments.
- Shrouded case design prevents shackle tampering.
- Stainless steel ball bearing tumblers lock both heel and toe sides of shackle for maximum strength.
- Available in non-key-retained (standard) and key-retained functions.
- All Oak padlocks accept the Oak IC core, as well as other SFIC cores.
- Uniquely tailored masterkey systems backed by extensive industry experienced system design and support.



SPECIFICATIONS:

Shackle Dimensions "D" = 3/8", "Y" = 25/32", "X" = 1"

Shackle Material Stainless Steel (standard)

Case Dimensions "W" = 2", "H" = 3 5/64", "T" = 1"

Case Material Precision machined from stainless steel (standard).

Function Non-key-retained (standard), optional key-retained field changeable.

Finishes 606 (Satin Brass), 626 (Satin Chrome), and 630 (Satin Stainless Steel)

Clevis & Chain Case mounted brass clevis optional. Brass or steel chains available.

IC Core Compatible with Oak IC core, and all other SFIC cores.

Masterkeying Tailored masterkey system set-up and design.



OAK HOW TO ORDER GUIDE – 41SP PADLOCK

41SP	-	0S		-	N	-	630	-	
Series	-	Shackle		-	Function	-	Case Finish	-	Options
		Height	Material						
41SP = Shrouded		0 = 1"	S = Stainless (opt)		R = Key Retained N = Non-Key Retained (std)		630 = Stainless		CS = Clevis/Chain - Steel 9" CB = Clevis/Chain - Brass 9"

Oak Security Group, LLC
8904 Bash Street, Suite K
Indianapolis, Indiana 46256

Toll-free: 877-OSG-LOCK
Phone: 317-585-9830
Fax: 317-585-9834

www.OakSecurity.com