



EXTRA HEAVY DUTY CYLINDRICAL LOCKSETS

Features

- Designed for high-traffic, vandal prone applications.
- Chassis can accommodate either Interchangeable core or Standard non-IC plug.
- Multiple latch backset choices available.
- Multiple finishes available.
- Non-handed.
- Stainless steel hubs to withstand over 1,000,000 cycles of operation.
- Independent torsion enhancing springs in hubs.
- Slabbed outside rose trim engages chassis to increase stability and durability.
- Inside and outside threaded rose liner and through bolt assembly for added strength.
- Adjustable through bolts for ease of installation
- Uniquely tailored masterkey systems backed by over 400 years of experienced system sales, design and support.
- 5 Year Warranty.



Specifications:

- Door Thickness** 1 3/8" to 2" wood or metal door
- Backsets** 2 3/4" (standard), 2 3/8", 3 3/4", 5" available
- Latchbolts** 1/2" throw, UL listed, self-adjusting faceplate
3/4" throw fire door latch available
- Strikes** ANSI (standard), T-strike and full lip strike also available
- Trim** Wrought brass knobs and roses, heavy gage inside and outside rose liners with through-bolted concealed screws. Rose is 3 1/2" diameter.
- IC Core** Interchangeable 6 & 7 pin compatible with all other small format interchangeable core housings
- Non-IC Plug** Standard "C" keyway, compatible with Schlage
- Masterkeying** Tailored masterkey system set-up and design. Construction cores available.
- Finishes** 605 (Bright Brass), 606 (Satin Brass), 612 (Satin Bronze), 613 (Dark Bronze), 625 (Bright Chrome) and 626 (Satin Chrome)
- Certification** UL listed "A" label (3 hour) single swing door (4'x8') ANSI A156.2, Series 4000 Grade 1

OAK HOW TO ORDER GUIDE – Extra Heavy Duty Knob Cylindrical Locksets

1CKX	2	EN	1	R	1	A	626	LC
------	---	----	---	---	---	---	-----	----

Series	Backset	Function	Core	Knob Type	Rose	Strike *	Finish	Keying
1CKX = Grade 1 Extra Heavy Duty Cylindrical Knob	2 = 2-3/8" 3 = 2-3/4" 4 = 3-3/4" 5 = 5"	CL = Classroom EN = Entrance ST = Storeroom See function chart for more functions	0 = None 1 = Oak Format IC 2 = Standard "C" Non-I/C plug	R = Round Knob	1 = Default	A = ANSI* T = T FLS = Full Lip Square FL4 = Full Lip 1/4"	605 606 612 613 625 626	LC = Less Core KE = Keyed

*ANSI standard with Grade 1

WWW.OAKSECURITY.COM

TOLL FREE (877) 674-5625

Manufacturers' registered trade names used above are for identification and reference only.

EXTRA HEAVY DUTY KNOB CYLINDRICAL LOCK FUNCTIONS

Function	Description	Operation Description
SINGLE KEYED		
	EN (F109) Entry/Office	Turn button locking: Pushing and turning the inside button clockwise locks the outside knob. Inside knob is always unlocked. Turning key in outside knob will retract latch. Push button locking: Pushing the inside button will lock outside knob. Inside knob is always unlocked. When button is pushed, turning inside knob or key in outside knob will release the button and latch.
	CL (F84) Classroom	Outside knob is locked or unlocked by rotating the key 360°. Inside knob is always unlocked.
	DO (90) Dormitory	Outside knob is locked by key in knob or by push button on inside knob. It is unlocked by key or by rotating inside knob. When locked by pushing the button on inside knob, closing the door will unlock the outside knob. Inside knob is always unlocked.
	ST (F86) Store Room	Outside knob is always locked. Turning key retracts latch. Inside knob is always unlocked.
DOUBLE KEYED		
	CO (F80) Communicating Lock	Turning key in either knob locks or unlocks its own knob independent of the other knob.
	IN (F87)) Institutional Lock	Both knobs always locked. Key in either knob retracts latch, but does not unlock knob.
	CS Classroom Security	Outside knob is locked and unlocked by key in outside knob. Inside knob always unlocked. Key in inside knob locks or unlocks outside knob.
	SD (F91) Store Door	Turning key in either side of door locks or unlocks both sides.
	VE (F88) Vestibule	Outside knob is locked or unlocked by key in inside knob. When outside knob is locked, key in outside knob will retract the latch. Inside knob is always unlocked.
NON-KEYED		
	PA (F75) Passage	Both sides always unlocked.
	PR (F76) Privacy	Both sides unlocked unless button on inside knob pushed. Closing door or turning emergency release in outside knob, or turning inside knob, releases button and unlocks outside knob.



Oak Security Group, LLC
8904 Bash Street, Suite K
Indianapolis, Indiana 46256

Toll-free: 877-OSG-LOCK
Phone: 317-585-9830
Fax: 317-585-9834

www.OakSecurity.com

Other Available Functions:

(Extended Lead Times)
EX – Exit Latch (F89)
HM – Hotel/Motel
PT – Patio (F77)
CR – Connecting Room
EN – Entrance w/ Push Button