

GRADE 1 MORTISE LOCKSETS

Features

- Heavy Duty (Grade 1) lock for Commercial and Industrial use.
- Levers and knobs are retained by lever/knob keeper similar to that of cylindrical locksets eliminating screw retaining problems.
- Independent lever return springs consistently return levers to horizontal position.
- Field reversible handing.
- Multiple functions, trim styles and finishes available.
- Roses and Full plate escutcheons are snap-on.
- Lever and Knob combinations are available.
- Uniquely tailored masterkey systems backed extensive industry experienced system design and support.
- 10 Year Warranty.





Specifications:

Certification UL listed for 3 Hour Fire Rating. ANSI A156.13 Series 1000 Grade 1 Operational.

Door Range 1 3/8" to 2 1/2" thick doors.

Case: 4-5/16" x 6" x 1", Face: 1-1/4" x 8" x 7/32", heavy wrought steel case with zinc dichromate

finish, field reversible handing, self-adjusting face for beveled doors

Backset 2 3/4"

Latchbolt 3/4" throw, 3-piece anti-friction design.

Deadbolt 1" throw, stainless steel.

Strike 1-1/4" x 4-7/8" curved lip, non-handed, standard strike for all functions, supplied with dust box.

Custom lip length at 1/8" increments available.

Spindles Designed to break when abused to prevent unlocking or damage to the case.

Trim Self-aligning through-bolt trim with independent lever return springs, snap-on roses/escutcheons.

Roses: (S1) 2 7/16" Diameter, (S2) 3 1/2" Diameter.

Full plate escutcheons: (F1) 1-15/16" x 8", (F2) 2-9/16" x 8-1/16"

IC Core OAK Interchangeable 6 & 7 pin core compatible with all other SFIC housings

IC Cylinder Standard 7 pin Interchangeable core housing, compatible with all SFIC cores.

Non IC Cylinder Standard "C" keyway, compatible with Schlage

Masterkeying Tailored masterkey system set-up and design. Construction cores available.

Finishes 605(Bright Brass), 606(Satin Brass), 612(Satin Bronze), 613(Dark Bronze), 625(Bright Chrome),

626(Satin Chrome), 630(Stainless Steel).

OAK HOW TO ORDER GUIDE - Grade 1 Mortise Locksets

1M	L	ENL	1	С	F2	CL	626	LC	
Series	Туре	Function	Core	Lever/Knob	Trim	Strike	Finish	Keying	Options
1M = Grade 1 Mortise Lockset	L =Lever	Latch CLL= Classroom	2 = Standard "C" Non-I/C plug	H = Hard returnC = Curved returnP = Tube LeverS = Straight	Escutcheon \$1 = SM Sect. Trim \$2 =Lgr	CL = Curved Lip (Std) CLL = Curved Lip - Spl Length- specify length	605 606 612 613 625 626 630	KE = Keyed	LM=Lost Motion R=RQE D=Door Position Monitor L=Latch Monitor

MORTISE FUNCTION CHART

Function	Description	Operation Description
SINGLE I	KEYED	
	ENL (F04) Entry/Office	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when not locked by thumbturn stopworks or key outside. Stopworks activated by thumbturn or key outside, locking outside lever/knob. Outside lever/knob remains locked until thumbturn is returned to the vertical position, or unlocked by key outside. Auxiliary latch deadlocks latchbolt when door is closed.
	END (F20) Entry/Office with Deadbolt	 Latchbolt always retracted by inside lever/knob for egress, or by key outside, or by outside lever/knob when not locked by thumbturn stopworks. Stopworks activated by partial thumbturn rotation, locking outside lever/knob. Outside lever/knob remains locked until thumbturn is returned to the vertical position. Full thumbturn rotation throws deadbolt, automatically locking the outside lever/knob. When deadbolt is thrown, key rotation outside or lever/knob rotation inside retracts deadbolt and latchbolt simultaneously. Auxiliary latch deadlocks latchbolt when door is closed.
	DCD (F13) Dormitory/Corridor	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when not locked by thrown deadbolt. Deadbolt thrown or retracted by key outside or thumbturn inside, automatically locking the outside lever/knob. When deadbolt is thrown, lever/knob rotation inside retracts deadbolt and latchbolt simultaneously, and unlocks outside lever/knob.
4	CHL (F06) Classroom Holdback	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob whe not locked by key outside. Outside lever/knob locked or unlocked by key outside. Rotate inside lever/knob and turn key one full turn to activate "holdback" feature. Auxiliary latch deadlocks latchbolt when door is closed.
	CLL (F05) Classroom	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob whe not locked by key outside. Outside lever/knob locked or unlocked by key outside. Auxiliary latch deadlocks latchbolt when door is closed.
-	SCD Storeroom/Closet w/ Deadbolt	 Latchbolt retracted by lever/knob from either side. Deadbolt thrown or retracted by key.
•	STD Storeroom with Deadbolt	 Latchbolt always retracted by inside lever/knob for egress, or by key outside. Outside lever/knob always inoperative. Deadbolt thrown or retracted by key outside or thumbturn inside. When deadbolt is thrown, lever/knob rotation inside retracts deadbolt and latchbolt simultaneously. Auxiliary latch deadlocks latchbolt when door is closed.
	STL (F07) Storeroom	 Latchbolt always retracted by inside lever/knob for egress, or by key outside. Outside lever/knob always inoperative. Auxiliary latch deadlocks latchbolt when door is closed.
DOUBLE	KEYED	
	CSD Classroom Security w/ Deadbolt	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when not locked by thrown deadbolt. Deadbolt thrown or retracted by key from either side, locking outside lever/knob. When deadbolt is thrown, lever/knob rotation inside retracts deadbolt and latchbolt simultaneously, and unlocks outside lever/knob



Oak Security Group, LLC 8904 Bash Street, Suite K Indianapolis, Indiana 46256

Toll-free: 877-OSG-LOCK Phone: 317-585-9830 Fax: 317-585-9834

	1	
	CSL Classroom Security	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when not locked by key from either side.
		Outside lever/knob locked by key from either side.
1 1		 Latchbolt can be retracted by key outside when locked.
		Auxiliary latch deadlocks latchbolt when door is closed.
	IND	Latchbolt retracted by key from either side.
	Institutional with	 Inside and outside lever/knob always inoperative. Deadbolt thrown or retracted by key from either side.
	Deadbolt	 Auxiliary latch deadlocks latchbolt when door is closed.
	INL (F30)	Latchbolt retracted by key from either side, but does not unlock lever/knob.
4	Institutional Lock	Inside and outside lever/knob always inoperative.
H		Auxiliary latch deadlocks latchbolt when door is closed.
	SUD (F14)	Latchbolt retracted by lever/knob from either side.
4	Store/Utility w/Dblt	Deadbolt thrown or retracted by key from either side.
H	Ctoror Ctimey W/Doil	2 Bouldon union in foliation by norm of more state.
lel	VEL (F09)	Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when
4	Vestibule	not locked by key inside.
H		 Outside lever/knob locked or unlocked by key inside.
1 1		 Latchbolt can be retracted by key outside when locked.
		Auxiliary latch deadlocks latchbolt when door is closed.
ELECTRI	FIED	
	STLEL	Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when
	Electrically Locked	unlocked by electronic device (12 or 24VAC) or power failure. (Fail Safe)
عاتم		Latchbolt can be retracted by key outside when locked.
		Auxiliary latch deadlocks latchbolt when door is closed.
4	STLEU Electrically Unlocked	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when unlocked by electronic device (12 or 24 VAC).
		 Latchbolt can be retracted by key outside when locked, or during power failure. (Fail Secure)
		 Auxiliary latch deadlocks latchbolt when door is closed.
NON-KEY	/ED	
	PRL Bath/Bedroom	Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when not locked by thumbturn stopworks.
H	Privacy	Stopworks activated by thumbturn inside, locking outside lever/knob.
		 Outside lever/knob remains locked until thumbturn is returned to the vertical position, or unlocked by rotating inside lever or closing door.
		To unlock from outside, insert emergency thumbturn in access hole and rotate.
•	PCL Privacy w/ Coin Turn	Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when not locked by key.
	Outside	Stopworks activated by thumbturn inside or coin turn outside, locking outside lever/knob.
		Outside lever/knob remains locked until thumbturn is returned to the vertical position, rotating coin turn outside, rotating inside lever or closing door.
		Auxiliary latch deadlocks latchbolt when door is closed.
		Function available in sectional trim only
	PAL Passage	Latchbolt always retracted by lever/knob from either side.



Oak Security Group, LLC 8904 Bash Street, Suite K Indianapolis, Indiana 46256

Toll-free: 877-OSG-LOCK Phone: 317-585-9830 Fax: 317-585-9834

	PRD Privacy w/ Deadbolt	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when not locked by thrown deadbolt.
		 Deadbolt thrown or retracted by thumbturn inside, locking outside lever/knob.
-		 When deadbolt is thrown, lever/knob rotation inside retracts deadbolt and latchbolt simultaneously, and unlocks outside lever/knob.
		 To unlock from outside, insert emergency thumbturn in access hole and rotate.
4.	PCD Privacy w/ Deadbolt	 Latchbolt always retracted by inside lever/knob for egress, or by outside lever/knob when not locked by thrown deadbolt.
ed in	and Coin Turn O/S	 Deadbolt thrown or retracted by thumbturn inside or coin turn outside, locking outside lever/knob.
		 When deadbolt is thrown, lever/knob rotation inside or coin turn outside retracts deadbolt and latchbolt simultaneously, and unlocks outside lever/knob.
		Function available in sectional trim only
DUMMY 1	TRIM	
	DTB	No latchbolt.
•	Single Dummy Trim	Inoperative lever/knob on one side of door used as pull.
4	DDB Double Dummy Trim	 No latchbolt. Inoperative lever/knob on both sides of door used as push/pull.



Oak Security Group, LLC 8904 Bash Street, Suite K Indianapolis, Indiana 46256

Toll-free: 877-OSG-LOCK Phone: 317-585-9830 Fax: 317-585-9834