

# **GRADE 2 TUBULAR DEADBOLTS**

### Features

- Deadbolt can be supplied with either Interchangeable core or standard non-IC cylinder.
- Double keyed function has concealed mounting screws.
- Strike plate supplied with standard 3" screws for enhanced security.
- Self-aligning installation in industry standard door prep.
- Uniquely tailored masterkey systems backed by extensive industry experienced system design and support.
- 5 Year Warranty.

# OAR

### Specifications:

| Door Thickness  | 1 3/8" to 2" wood or metal door  |  |  |  |  |  |
|-----------------|--|--|--|--|--|--|
| Backsets        | 2 3/8" (standard), or 2 3/4" available   |  |  |  |  |  |
| Bolts           | <ul> <li>1" throw on 2 3/4" BS with 1 1/8"x 2 1/4" faceplate.</li> <li>1" throw on 2 3/8" BS with 1"x 2 1/4" faceplate.</li> </ul> |  |  |  |  |  |
| Strikes         | Square corner (standard) or radius corner plate available.   |  |  |  |  |  |
| Rings           | Brass tapered rings.   |  |  |  |  |  |
| IC Core         | Interchangeable 6 & 7 pin compatible with all other small format interchangeable core housings                                     |  |  |  |  |  |
| Non-IC Cylinder | r Standard "C" keyway, compatible with Schlage   |  |  |  |  |  |
| Masterkeying    | g Tailored masterkey system set-up and design. Construction cores available.   |  |  |  |  |  |
| Finishes        | 605(Bright Brass), 606(Satin Brass), 612(Satin Bronze), 613(Dark Bronze), 625(Bright Chrome)<br>and 626(Satin Chrome)              |  |  |  |  |  |
| Certification   | tion UL listed "A" label (3 hour) single swing door (4'x8').   |  |  |  |  |  |

### OAK HOW TO ORDER GUIDE - Grade 2 Deadbolt Locks

| 2DB                                 | 2                 | к        | 1  | SC   | 626                                    | LC                           |
|-------------------------------------|-------------------|----------|--|--|--|------------------------------|
| Series                              | Backset           | Function | Core   | Strike                                       | Finish                                 | Keying                       |
| <b>2DB =</b><br>Grade 2<br>Deadbolt | <b>3</b> = 2-3/4" |          | 1= Oak Format<br>I/C<br>2 = Standard<br>Non I/C plug | SC= Square<br>Corner<br>RC= Radius<br>Corner | 605<br>606<br>612<br>613<br>625<br>626 | LC = Less Core<br>KE = Keyed |

<u>WWW.OAKSECURITY.COM</u> Manufacturers' registered trade names used above are for identification and reference only. TOLL FREE (877) 674-5625

## DEADBOLT LOCK FUNCTIONS

| Function     | Description   | Operation Description  |  |  |  |  |
|--------------|---|--|--|--|--|--|
| SINGLE KEYED |   |  |  |  |  |  |
| o (i)        | K (E2151/181K)<br>Key/ Thumb Turn                     | Locked or unlocked by turning key 360° in outside cylinder, or turning inside thumb turn   |  |  |  |  |
| o į          | L (E2161/181L)  | Locked or unlocked by turning key 360° in outside cylinder. Inside is blank.   |  |  |  |  |
| c (i)        | <b>S (E2171/181S)</b><br>Classroom<br>Key/ Thumb Turn | Locked or unlocked by turning key 360° in outside cylinder. Inside thumbturn will unlock door only.<br>You can not lock door with the thumbturn. |  |  |  |  |
| DOUBLE       | DOUBLE KEYED  |  |  |  |  |  |
| o jo         | M (E2141/181M)<br>Keyed Both Sides                    | Locked or unlocked by turning key in either side 360°.   |  |  |  |  |



Oak Security Group, LLC 8904 Bash Street, Suite K Indianapolis, Indiana 46256

Toll-free: 877-OSG-LOCK Phone: 317-585-9830 Fax: 317-585-9834

www.OakSecurity.com